



ANGLES (Bar Sizes)



PER ASTM A-36
58,000/80,000 PSI
STOCK LENGTH - 20'

Size in Inches	Weight Per Foot (Lbs)
1/2 X 1/2 X 1/8	.38
3/4 X 3/4 X 1/8	.59
7/8 X 7/8 X 1/8	.70
1 X 1 X 1/8	.80
1 X 1 X 3/16	1.16
1 X 1 X 1/4	1.49
1-1/4 X 1-1/4 X 1/8	1.01
1-1/4 X 1-1/4 X 3/16	1.48
1-1/4 X 1-1/4 X 1/4	1.92
1-3/8 X 7/8 X 1/8	.91
1-3/8 X 7/8 X 3/16	1.32
1-1/2 X 1-1/4 X 3/16	1.64
1-1/2 X 1-1/2 X 1/8	1.23
1-1/2 X 1-1/2 X 3/16	1.80
1-1/2 X 1-1/2 X 1/4	2.34
1-3/4 X 1-1/4 X 1/8	1.23
1-3/4 X 1-1/4 X 3/16	1.80
1-3/4 X 1-1/4 X 1/4	2.34
1-3/4 X 1-3/4 X 1/8	1.44
1-3/4 X 1-3/4 X 3/16	2.12
1-3/4 X 1-3/4 X 1/4	2.77
2 X 1-1/4 X 3/16	1.96
2 X 1-1/4 X 1/4	2.55
2 X 1-1/2 X 1/8	1.44
2 X 1-1/2 X 3/16	2.12
2 X 1-1/2 X 1/4	2.77
2 X 2 X 1/8	1.65
2 X 2 X 3/16	2.44
2 X 2 X 1/4	3.19
2 X 2 X 5/16	3.92
2 X 2 X 3/8	4.70
2-1/2 X 1-1/2 X 3/16	2.44
2-1/2 X 1-1/2 X 1/4	3.19
2-1/2 X 1-1/2 X 5/16	3.92
2-1/2 X 2 X 3/16	2.75
2-1/2 X 2 X 1/4	3.62
2-1/2 X 2 X 5/16	4.50
2-1/2 X 2 X 3/8	5.30
2-1/2 X 2-1/2 X 3/16	3.07
2-1/2 X 2-1/2 X 1/4	4.10
2-1/2 X 2-1/2 X 5/16	5.00
2-1/2 X 2-1/2 X 3/8	5.90
2-1/2 X 2-1/2 X 1/2	7.70

ANGLES (Structural)




PER ASTM A-36
58,000/80,000 PSI
STOCK LENGTHS - 20', 30', 40'

Size in Inches	Weight Per Foot (Lbs)
3 X 2 X 3/16	3.07
3 X 2 X 1/4	4.1
3 X 2 X 5/16	5.0
3 X 2 X 3/8	5.9
3 X 2 X 1/2	7.7
3 X 2-1/2 X 1/4	4.5
3 X 2-1/2 X 5/16	5.6
3 X 2-1/2 X 3/8	6.6
3 X 3 X 3/16	3.71
3 X 3 X 1/4	4.9
3 X 3 X 5/16	6.1
3 X 3 X 3/8	7.2
3 X 3 X 1/2	9.4
3-1/2 X 2-1/2 X 1/4	4.9
3-1/2 X 2-1/2 X 5/16	6.1
3-1/2 X 2-1/2 X 3/8	7.2
3-1/2 X 2-1/2 X 1/2	9.4
3-1/2 X 3 X 1/4	5.4
3-1/2 X 3 X 5/16	6.6
3-1/2 X 3 X 3/8	7.9
3-1/2 X 3 X 1/2	10.2
3-1/2 X 3-1/2 X 1/4	5.8
3-1/2 X 3-1/2 X 5/16	7.2
3-1/2 X 3-1/2 X 3/8	8.5
3-1/2 X 3-1/2 X 1/2	11.1
4 X 3 X 1/4	5.8
4 X 3 X 5/16	7.2
4 X 3 X 3/8	8.5
4 X 3 X 1/2	11.1
4 X 3-1/2 X 1/4	6.2
4 X 3-1/2 X 5/16	7.7
4 X 3-1/2 X 3/8	9.1
4 X 3-1/2 X 1/2	11.9
4 X 4 X 1/4	6.6
4 X 4 X 5/16	8.2
4 X 4 X 3/8	9.8
4 X 4 X 1/2	12.8
4 X 4 X 5/8	15.7
4 X 4 X 3/4	18.5
5 X 3 X 1/4	6.6
5 X 3 X 5/16	8.2
5 X 3 X 3/8	9.8
5 X 3 X 1/2	12.8

ANGLES (Structural - continued)

Size in Inches	Weight Per Foot (Lbs)
5 X 3-1/2 X 1/4	7.0
5 X 3-1/2 X 5/16	8.7
5 X 3-1/2 X 3/8	10.4
5 X 3-1/2 X 1/2	13.6
5 X 3-1/2 X 5/8	16.8
5 X 3-1/2 X 3/4	19.8
5 X 5 X 5/16	10.3
5 X 5 X 3/8	12.3
5 X 5 X 1/2	16.2
5 X 5 X 5/8	20.0
5 X 5 X 3/4	23.6
6 X 3-1/2 X 5/16	9.8
6 X 3-1/2 X 3/8	11.7
6 X 3-1/2 X 1/2	15.3
6 X 4 X 5/16	10.3
6 X 4 X 3/8	12.3
6 X 4 X 1/2	16.2
6 X 4 X 5/8	20.0
6 X 4 X 3/4	23.6
6 X 6 X 3/8	14.9
6 X 6 X 1/2	19.6
6 X 6 X 5/8	24.2
6 X 6 X 3/4	28.7
6 X 6 X 7/8	33.1
6 X 6 X 1	37.4
7 X 4 X 3/8	13.6
7 X 4 X 1/2	17.9
7 X 4 X 3/4	26.2
8 X 4 X 1/2	19.6
8 X 6 X 1/2	23.0
8 X 6 X 3/4	33.8
8 X 6 X 1	44.2
8 X 8 X 1/2	26.4
8 X 8 X 5/8	32.7
8 X 8 X 3/4	38.9
8 X 8 X 1	51.0

PERFORATED GALVANIZED ANGLES



Each flange is punched with a 13/32" diameter hole on 1" centers which will accept a 3/8 diameter bolt.

STOCK LENGTH - 10'

Size in Inches	Weight Per Piece (Lbs)
1-1/4 X 1-1/4 X 14 Gauge	5.53
1-1/2 x 1-1/2 x 12 Gauge	9.12
2 X 2 X 12 Gauge	12.60