


HOT ROLLED ROUNDS




PER ASTM A-36
58,000/80,000 PSI
STOCK LENGTH - 20'

Size in Inches	Weight Per Foot (Lbs)	Size in Inches	Weight Per Foot (Lbs)
1/4	.167	2-1/2	16.69
5/16	.261	2-5/8	18.40
3/8	.376	2-3/4	20.19
7/16	.511	2-7/8	22.07
1/2	.668	3	24.03
9/16	.845	3-1/8*	26.08
5/8	1.043	3-1/4*	28.21
3/4	1.502	3-3/8*	30.42
13/16	1.763	3-1/2*	32.71
7/8	2.045	3-5/8*	35.09
15/16	2.347	3-3/4*	37.55
1	2.670	3-7/8*	40.10
1-1/8	3.380	4*	42.73
1-3/16	3.767	4-1/8*	45.44
1-1/4	4.172	4-1/4*	48.23
1-5/16	4.603	4-3/8*	51.11
1-3/8	5.049	4-1/2*	54.08
1-1/2	6.008	4-5/8*	57.12
1-5/8	7.051	4-3/4*	60.25
1-3/4	8.178	5*	66.76
1-7/8	9.388	5-1/4*	73.60
2	10.68	5-1/2*	80.78
2-1/8	12.06	5-3/4*	88.29
2-1/4	13.52	6*	96.13
2-3/8	15.06		

* Supplied as a C-1018 not an A-36

HOT ROLLED SQUARES



PER ASTM A-36
58,000/80,000 PSI
STOCK LENGTH - 20'

Size in Inches	Weight Per Foot (Lbs)	Size in Inches	Weight Per Foot (Lbs)
3/8	.478	1-3/4	10.413
7/16	.651	2	13.60
1/2	.851	2-1/4	17.21
9/16	1.076	2-1/2	21.25
5/8	1.329	2-3/4	25.71
3/4	1.914	3	30.60
7/8	2.605	3-1/2	41.65
1	3.402	4	54.40
1-1/8	4.306	4-1/2	68.85
1-1/4	5.316	5	85.00
1-1/2	7.655	6	122.40